## OPTIC HAND DRYER SPEED-DRY

## BLINDER LINE STEEL







REF: CS-600-I/X BRIGHT STAINLESS STEEL Finish



REF: CS-600-S/X SATIN STAINLESS STEEL Finish

- This model SPEED-DRY	of Blinder	Line	of	hand-held,	has
narrow air outlet.					

- Ecofrendly system, saves time and consumption. Thanks to a temperature sensor, from approx. 25  $^{\circ}$  C, desactivates the hot air mode.
- It has a compact design, robust and with vandal-proof features
- Suitable for toilets with high and intense traffic.
- Maximum power and airflow.

**GENERAL DESCRIPTION** 

- Different finishes: WHITE LACQUERED METAL, STAINLESS STAINLESS STEEL and BRIGHT STAINLESS STEEL.
- Operates by activating a proximity sensor.
- Approvals: CE and SGS.

12011110712 201 2011 1071110110						
Material	METAL / STAINLESS STEEL					
Power	1.650 W					
Voltage	220 - 240 V					
Frecuency	50/60 Hz					
Degree of protection	IP21					
Sound level (2 meters)	75,5 dB					
Air temperature (Ta=21 °C)	20-40 °C					
Airflow	227 m <sup>3</sup> /h					
Velocity	396 km/h					
Electrical isolation	Class I					
System	Sensor. Powered by proximity					
Drying time	8-12 seconds					

TECHNICAL ESPECIFICATIONS

MEASUREN	MENTS				WEIGHT	VOLUME	
PRODUCT	y	<b>x</b> 295 mm	<b>y</b> 325 mm	<b>z</b> 172 mm	NET WEIGHT: 4,3 kg (without packaging)	-	
BOX (1 Unit)		<b>X</b> 330 mm	<b>y</b> 370 mm	<b>z</b> 215 mm	GROSS WEIGHT: 5 kg (with packaging)	0,0326 m <sup>3</sup>	
STANDARD E (4 Units)	30X	<b>X</b> 680 mm	<b>y</b> 400 mm	<b>z</b> 455 mm	21 kg	0,12 m <sup>3</sup>	
PALLET		<b>x</b> 1360 mm	<b>y</b> 1750 mm	<b>z</b> 910 mm	-	2,126 m <sup>3</sup>	
DETAILS					UNITS		
		PALLET LAYERS			64		
PALLET		UNITS			4		
		BOXES PER LAYERS			4		
APPROVED BY: Technical department			<b>DATE</b> : 25/07/	2017	F 03.08.03		